







High-Performance & High Quality with Low-Price

- Solid and Tough body
- Large Displays
- Absolute Encoders
- Versatile Field Application Software
- Alphanumeric Key for Quick Data Input
- Long Life Battery



High Accuracy & Long Measuring Range

Long distance: 2,000m with Single Prism Higher accuracy: ±(2mm+2ppm)

Versatile Application Programs

- On-board data collection, Stakeout/Survey, Road Calculation, and many more functions.
- Integrated Alphanumeric keyboard realizes the quicker operation.
- Large internal memory up to 24,000 pts

Enhanced Absolute Encoder

Adopted absolute encoder, which doesn't require 0 set. Thanks to this encoder, it can realize stable measurement with less reading error.

Superior Waterproof; Dustproof

Applied to IEC Standard IP54. No worry about sudden bad weather.

STANDARD COMPONENTS



GTS-102N(with lens cap) On-board Battery BT-G1 Battery Charger BC-G1C Plastic Carrying Case Tool kit with case Plastic rain cover Silicon cloth





TOPCON CORPORATION 75-1 Hasunuma-cho, Itabashi-ku, Tokyo 174-8580, Japan Phone: (+81)3-3558-2993 Fax: (+81)3-3965-6898 www.topcon.co.jp

TOPCON SOKKIA INDIA PVT. LTD. C-25, GROUND FLOOR, SECTOR-8, NOIDA, U.P. - 201 301 www.topconsokkia.ind.in

Specifications subject to change without notice ©2011 Topcon Corporation All rights reserved. P-103-1



GTS-102N

TELESCOPE	
Length	150mm
Objective Lens	Dia. 45mm (EDM50mm)
Magnification	30x
Field of View	1°30′
Resolving Power	3.0"
Minimum Focus	1.3m
DISTANCE MEASUREMENT*	
Mini Prism	900m
1 Prism	2000m
3 Prisms	2700m
*Slight haze with visibility about 20km moderate sunlight with light heat shimmer.	
Accuracy	±(2mm+2ppmxD)m.s.e
ANGLE MEASUREMENT	
Accuracy	2″
Method	Absolute Reading
Detecting System (H)	Dual
Detecting System (V)	Single
Minimum Reading	5″/1″
Tilt Correction	Single Axis
OTHERS	
Display Unit	Graphics LCD 160x64 Dots, 2 Sides
Keyboard	Alpha-Numeric key
Dimension	336(H)x184(w)x172(L)mm
Weight	4.9kg (with battery)
Durability	
Protection against dust & water	IP54 (Based on the standard IEC60529)
Operating Temperature	-20°C to +50°C
Internal Memory	24,000pts
BATTERY BT-G1	
Operation Time	8 hours
BATTERY CHARGER BC-G1C	
Input Voltage	AC230V
Recharging time	1.8 hours (+10°C to +40°C)

Your local Authorized Topcon Dealer is: Kohinoor Enterprises Mob.-09897251201,09027030665,01332-260897 Email.-kohinooren@gmail.com web.-www.kohinoorinstruments.com