



Suitable for outdoor as well as for indoor use the user friendly AT-24 Auto Level Series from SETL is your guarantee to get the job done, accurate and on time.

Built to Last

With the AT-24 Series SETL introduces an automatic level to the construction industry designed for your daily levelling tasks with outstanding price-to-performance ratio.

Meeting the IP54 class specifications guarantees all weather operation of the AT-24 Series and provides you with an instrument that “Works when you do!”.

Specification

Model Parameter	AT-20	AT-24	AT-28
Standard Deviation for 1km Double-run levelling	2.5mm	2.0mm	2.0mm
Telescope image	Erect	Erect	Erect
Magnification	20X	24X	24X
Clear Objective Aperture	30mm	30mm	30mm
Angle of field of View	1°20'	1°20'	1°20'
Shortest Focusing Distance	0.6m	0.6m	0.6m
Stadia Multiplying Constant	100	100	100
Stadia Additive Constant	0	0	0
Sensitivity of Circular Level	8'/2mm	8'/2mm	8'/2mm
Graduation interval of Circle	1°or 1gon	1°or 1gon	1°or 1gon
Compensator type	magnetic-damping		
Compensator working Range	±15'	±15'	±15'
Setting Accuracy	±0.5"	±0.5"	±0.5"
Dimensions	190×130×136mm	190×130×136mm	190×130×136mm
Weight	1.22kg	1.22kg	1.22kg
Connecting size to tripod	M16 or 5/8"	M16 or 5/8"	M16 or 5/8"

Kohinoor Enterprises, Roorkee

Mob.-09897251201,09027030665,01332-260897

Email.-kohinooren@gmail.com

Web.-www.surveyinstrument.net